



Acer P1258i - 4800 Ansi lumen - XGA Projector

SKU	MR.JYF11.002
Brand	Acer
Stock	In stock

PRICING

Sign in to view pricing.

Description

Extended product overview

Designed for business settings, the Acer P1258i delivers vivid presentations with 4,800 lumens, wireless projection, 1.3x zoom, XGA resolution, and 24/7 reliability for all your meetings. 4,800 Lumens Brightness See crystal-clear, vibrant images from a distance in daylight or medium to large rooms with up to 4,800 lumens of brightness. Wireless Projection [1][2] Break free from the clutter of wires with easy wireless projection options and wireless dongle design [1] [2] . 1.3x Zoom Ratio Maximize your space with a zoom ratio that's ideal for mid-sized meeting rooms. XGA Resolution Even at long distances, this projector delivers a sharp and crisp image quality with its 1024x768 XGA resolution. Acer ColorSafe II Enjoy consistent, natural colors with ColorSafe II technology, which controls the dynamic RGB levels to prevent color decay. Acer LumiSense™ Acer LumiSense™ adjusts the image brightness and color saturation based on the content you're viewing. Acer BlueLightShield™ Protect your eyes from unnecessary strain by utilizing Acer BlueLightShield™ technology. Automatic Vertical Keystone Correction Finding the right angle for your presentation is easier with auto keystone correction, which corrects vertical distortion. 24/7 Operation [3] This projector handles continuous day in, day out use - ideal for public displays and exhibitions. .full-spec-container { width: 100%; margin: 20px 0; font-family: -apple-system, BlinkMacSystemFont, "Segoe UI", Roboto, Arial, sans-serif; line-height: 1.5; } .full-spec-table { width: 100%; border-collapse: collapse; border: 1px solid #e1e1e1; font-size: 14px; color: #333; } .full-spec-table thead th { background-color: #333; color: #fff; text-align: left; padding: 12px; text-transform: uppercase; font-size: 13px; letter-spacing: 1px; } .full-spec-table td { padding: 10px 15px; border-bottom: 1px solid #eee; vertical-align: top; } .spec-name { background-color: #f9f9f9; font-weight: 600; width: 35%; color: #555; border-right: 1px solid #eee; } .spec-data { width: 65%; background-color: #fff; } .full-spec-table tr:last-child td { border-bottom: none; } @media (max-width: 600px) { .spec-name { width: 45%; font-size: 13px; } .spec-data { font-size: 13px; } } Display / Image Projection System System DLP™ Light Source OSRAM 240 W E30.1 Light Source Life 5000 hours (Standard), 10000 hours (ECO) Native Resolution 1024 x 768 Maximum Resolution 1920 x 1200 Brightness 4800 ANSI Lumens (Standard), 3840 lm (ECO), (Compliant with ISO 21118 standard) Aspect Ratio 4:3 (Native), 16:9 (Supported) Contrast Ratio 20,000:1 Image Size 26" (66 cm) ~ 266" (675.6 cm) Keystone Correction +/- 40° (Vertical, Manual & Auto) Throw Ratio 1.48 to 1.93 (1295.4 mm @ 2000 mm) Zoom Ratio 1.3x Digital Zoom Detail Digital Zoom & ImageShift (0.7X-1.0X) Lens F = f/2.43~f/2.78, f = 16.90 mm~21.61 mm, Manual Zoom, Manual Focus Projection Offset 130% (Half-Height) Projection Mode Front, Front Ceiling, Rear, Rear Ceiling Vertical Sync Rate 24 ~ 120 Hz Horizontal Sync Rate 15 to 100 kHz Interfaces / Ports HDMI HDMI1.4b (HDCP 1.4) Component x1 RCA Video x1, RCA Audio In x1, 3.5mm mini jack Audio Out x1, 3.5mm mini jack S/PDIF Included USB Type-A In USB (Wireless dongle, Hidden Type A 2.0) x 1 USB Type-A Out x1, DC Out (5V/1.5A) Speaker x1, 10 W Speaker Control, Network & General RS232 x1, D-sub 3D Support DLP 3D Ready, HDMI 3D Ready, 144Hz 24p 3D Security Security Bar, Kensington Lock Input Lag 16.7ms @ 60Hz Installation Ceiling Mountable Weight 2.8 kg (6.2 lb) Power Description Power Consumption 290 Watts (Standard), 210 Watts (ECO), 0.5 Watts (Standby) Miscellaneous & Accessories Optional Accessories Lamp (MC.JTG11.003) Standard Accessories P1258i DLP Projector, AC Power Cord, Battery for remote control, HDMI Cable, Lens Cap, Quick Start Guide, Remote Control, Security Card, Carrying Case, WirelessProjection-Kit (UWA5)