



**Acer X1128H - DLP projector - 3D - SVGA (800 x 600)**

SKU	MR.JTG11.002
Brand	Acer
Stock	In stock

PRICING

Sign in to view pricing.

## Description

Extended product overview

Project with clarity with the X1128H projector. Get bright, clear images even in well-lit, medium-sized rooms with up to 4,800 lumens of brightness. True-to-life colors are possible thanks to Acer LumiSense™, ColorBoost3D™, and Color Safe II, while Acer BlueLightShield™ protects your eyes. 4,800 Lumens Brightness See crystal-clear, vibrant images from a distance in daylight or medium to large rooms with up to 4,800 lumens of brightness. Acer ColorBoost3D™ Reproduce lifelike colors and brilliantly bright images with Acer ColorBoost3D™ technology. Acer ColorSafe II Enjoy consistent, natural colors with ColorSafe II technology, which controls the dynamic RGB levels to prevent color decay. Acer LumiSense™ Acer LumiSense™ adjusts the image brightness and color saturation based on the content you're viewing. Acer BlueLightShield™ Protect your eyes from unnecessary strain by utilizing Acer BlueLightShield™ technology. Integrated Speakers [1] What you hear will be just as good as what you see with the powerful built-in speakers. [1] Specifications vary depending on model and/or region.

Display / Image Projection System	System DLP™	Light Source	220 W	Light Source Life	6000 hours (Standard), 10000 hours (ECO)	Native Resolution	800 x 600	Maximum Resolution	1920 x 1200	Brightness	4800 ANSI Lumens (Standard), 3600 lm (ECO)	Aspect Ratio	4:3 (Native), 16:9 (Supported)	Contrast Ratio	20,000:1	Image Size	23" (58.4 cm) ~ 7.62 m (300")	Throw Ratio	1.94 to 2.16 (1295.4 mm @ 2000 mm)	Zoom Ratio	1.1x	Lens F = f/2.41~f/2.53, f = 21.85 mm~24.01 mm	Manual Zoom	Manual Focus	Projection Offset	130% (Half-Height)	Projection Mode	Front, Rear, Ceiling, Rear Ceiling	Vertical Sync Rate	24 ~ 120 Hz	Horizontal Sync Rate	15 to 100 kHz	Interfaces / Ports	VGA In x1, D-sub VGA Out x1, D-sub Video x1, RCA Audio In x1, 3.5mm mini jack Audio Out x1, 3.5mm mini jack S/PDIF	Included Power & Physical Characteristics	Power Consumption	275 Watts (Standard), 205 Watts (ECO), 0.5 Watts (Standby)	Installation	Ceiling Mountable	Weight (Approximate)	2.8 kg (6.2 lb)	Miscellaneous	Optional Accessories	Carrying Case (MC.JPV11.005), Lamp (MC.JR711.008)
[1] Specifications vary depending on model and/or region.																																												