



BenQ MH550 3500 Ansi Lumens 1080P Projector

SKU	9H.JJ177.1HE
Brand	BenQ
Stock	In stock

PRICING

Sign in to view pricing.

Description

Extended product overview

The BenQ MH550 is a high-performance business projector designed to deliver exceptional presentations with its advanced features and user-friendly design. With a brightness of 3,500 ANSI lumens and a high contrast ratio of 20,000:1, the MH550 ensures clear and vibrant images, even in well-lit meeting rooms. This projector offers Full HD resolution (1920x1080) with a native 16:9 aspect ratio, providing sharp and detailed visuals suitable for various presentation formats. Equipped with dual HDMI inputs, the MH550 allows seamless connectivity with multiple devices, facilitating flexible multimedia presentations. BenQ's SmartEco technology intelligently adjusts lamp power consumption, reducing energy usage by up to 70% without compromising picture quality. This not only extends the lamp life but also lowers maintenance costs, making the MH550 an energy-efficient choice for businesses. The MH550 features Auto Vertical Keystone correction, which automatically aligns the image to a perfectly squared shape, even when the projector is placed at an angle. Additionally, the retractable adjustment foot provides enhanced flexibility, allowing easy setup in various meeting room configurations. For added convenience, the projector includes a USB Type-A port with a 1.5A power supply, enabling charging of smart devices during meetings. The inclusion of a Kensington Lock ensures the device is secure, deterring potential theft. With its combination of high brightness, versatile connectivity, energy-saving features, and user-friendly design, the BenQ MH550 is an ideal solution for professional presentations and business meetings.

All Specifications Display Brightness (ANSI lumens) 3500 Resolution 1080P (1920x1080) Native Aspect Ratio 16:9 Contrast Ratio (FOFO) 20,000:1 Display Color 30-bit (1.07 billion colors) Light Source Lamp Light Source Life Normal 5000 hrs, ECO 10000 hrs, SmartEco 10000 hrs, LampSave 15000 hrs Optical Throw Ratio 1.49~1.64 Zoom Ratio 1.1x Lens F/# = 2.56 ~ 2.68, f = 22 ~ 24.1 mm Projection Offset 100% Keystone Adjustment 1D, Vertical ± 30 degrees Picture Picture Modes 3D, Bright, Infographic, Presentation, sRGB, User 1, User 2 Compatibility Resolution Support VGA(640 x 480) to WUXGA_RB(1920 x 1200) Horizontal Frequency 15K~102KHz I/O Interface PC in (D-sub 15pin) 1 Monitor out (D-sub 15pin) 1 Composite Video in (RCA) 1 S-Video in (Mini DIN 4pin) 1 HDMI in 2 (HDMI-1 & HDMI-2: 1.4a/HDCP1.4) USB Type Mini B 1 RS232 in (DB-9pin) 1 Audio Speaker 2W Audio in (3.5mm) 1 Audio out (3.5mm) 1 Environment Operating Temperature 0~40 Power Supply AC 100 to 240 V, 50/60 Hz Typical Power Consumption (110V) ~260W Acoustic Noise (Typ./Eco.) 33 / 29 dB Accessories Remote Control w/ Battery RCX014 Power Cord 1 (1.8M) VGA Cable 1 (1.5M) User Manual CD 1 (24L) 3D Glasses DGD5 (Optional) Quick Start Guide 1 (18L) Warranty Card Included (by region) Universal Ceiling Mount CM00G3 (Optional) Dimension & Weight Dimensions (WxHxD) 296 x 120 x 221 mm Net Weight 2.3 kg Projection System Projection System DLP