



Viewsonic LS832WU Ultra Short Throw 5000 ANSI Lumen Laser Projector

SKU	LS832WU
Brand	ViewSonic
Stock	In stock

PRICING

Sign in to view pricing.

Description

Extended product overview

The LS832WU is part of ViewSonic's Luminous Superior series, a lamp-free high-brightness projector lineup designed for both commercial and educational spaces. This advanced 5,000 ANSI lumens WUXGA ultra short-throw laser projector is a go-to digital signage solution for public and commercial applications, such as museums, storefronts, shopping malls, and airports. The LS832WU's 0.25 ultra-short throw ratio allows for a 100" screen from only 28 cm away, and the screen size can be further expanded up to 170", offering a lower cost-per-inch compared to other types of commercial displays. Adopting the 2nd generation Laser Phosphor technology, it produces consistent high brightness for up to 30,000 hours lifespan. With H/V keystone and 4-corner image adjustment, the LS832WU also offers flexible installation options. Complete with comprehensive LAN control, it enables centralised management of multiple devices and is compatible with Crestron, AMX, Extron, and PJ Link AV control systems. Specifications Projection System: 0.67" WUXGA Native Resolution: 1920x1200 Brightness: 5000 (ANSI Lumens) Contrast Ratio: 3000000:1 Display Color: 1.07 Billion Colours Light Source Type: Laser Phosphor Light Source Life (hours) with Normal Mode: 20000 Light Source Life (hours) with SuperEco Mode: 30000 Lens: F=2.44, f=3.70mm Projection Offset: 133%±3% Throw Ratio: 0.253 Optical Zoom: Fixed Digital Zoom: 0.8x-2.0x Image Size: 80"- 170" Throw Distance: 0.17-0.66m (100"@0.28m) Keystone: H:±10°, V:±10° Audible Noise (Normal): 34dB Audible Noise (Eco): 28dB Input Lag: 33.2ms Resolution Support: VGA(640 x 480) to 4K(3840 x 2160) HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p Horizontal Frequency: 15K- 91KHz Vertical Scan Rate: 24- 85Hz Input Computer in (share with component): 1 HDMI: 2 (HDMI 2.0/ HDCP 1.4/2.2) Audio-in (3.5mm): 1 Microphone in: 1 Output Monitor out: 1 Audio-out (3.5mm): 1 Speaker: 10W x1 USB Type A (Power): 1 (5V/1.5A) Control RS232 (DB 9-pin male): 1 RJ45 (LAN control): 1 USB Type B (Services): 1 Others Power Supply Voltage: 100-240V±10%, 50/60Hz (AC in) Power Consumption: Normal: 328W Standby: <0.5W Operating Temperature: 5~40 Carton: Brown Net Weight: 5.8kg Gross Weight: 8.1kg Dimensions (WxDxH) with Adjustment Foot: 382x318x132mm Packing Dimensions: 518x420x313mm OSD Language: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Swedish, Norwegian, Finnish, Greek, T Chinese, S Chinese, Japanese, Korean, Russian, Hungarian Czech, Arabic, Thai, Turkish, Farsi, Vietnam, Indonesian, Romania, Slovakian (27 languages) User Guide Language: English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages Accessories Power Cord: 1 Remote Control: 1 QSG: Yes Warranty Card: Yes (CN Only)