

PRODUCT OVERVIEW

ViewSonic LS901HD 6,000 ANSI Lumens 1080p Laser Installation Pro- jector

ViewSonic • SKU LS901HD



ViewSonic LS901HD 6,000 ANSI Lumens 1080p Laser Installation Projector

SKU	LS901HD
Brand	ViewSonic
Stock	In stock

PRICING

Sign in to view pricing.

Description

Extended product overview

Introducing the LS901HD from ViewSonic's Luminous Superior Series, tailored for expansive venue displays. Featuring a robust 6,000 ANSI Lumens brightness and high native contrast provided by a 0.65" DMD chip through DLP technology, it delivers stunning visuals on screens up to 300-inch. With a 1.7x optical zoom, it allows for a flexible setup to suit various installation needs, and the vertical lens shift and H/V keystone adjustment make the process a breeze. Additionally, portrait mode and 360° projection capabilities cater to more advanced requirements. Comprehensive LAN control ensures seamless integration into existing device management networks. The projector also features HDMI 2.0b, allowing you to enjoy original 4K quality content with HDR and HLG support. Employing advanced 3rd generation laser phosphor technology, the LS901HD boasts a remarkable 30,000-hour lifespan, reducing maintenance costs for both business and educational institutions.

Key Features: 6,000 ANSI Lumens ensure vibrant images in large venues High native contrast ratio provided by a 0.65" DMD chip and DLP technology 3rd generation laser phosphor technology with up to a 30,000-hour lifespan Installation flexibility: 1.7x zoom, V lens shift, H/V keystone correction, and 360° projection Centralized LAN control for efficient management HDMI 2.0b enables 4K HDR/HLG content playback

Specification Details

Projection System 0.65" 1080p Native Resolution 1920x1080 Brightness 6000 (ANSI Lumens) Brightness (Center Lumens) 6600 Contrast Ratio 3000000:1 Display Color 1.07 Billion Colors Light Source Type Laser Phosphor Light Source Life (Normal Mode) 20000 hours Light Source Life (SuperEco Mode) 30000 (Eco) Lens F=2.3-3.0, f=17.63-27.9mm Projection Offset 154% +/- 10% Throw Ratio 1.2-2.04 Optical Zoom 1.7X Digital Zoom 0.8x-2.0x Image Size 30"-300" Throw Distance 0.80-13.55m (100"@2.66m) Keystone H: +/-30°, V: +/-30° Lens Shift V. Range 0%, -21% Audible Noise (Normal) 31dB Audible Noise (Eco) 25dB Input Lag 16ms Resolution Support VGA(640 x 480) to 4K UHD(3840 x 2160) HDTV Compatibility 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p Horizontal Frequency 15K-135KHz Vertical Scan Rate 23-120Hz HDMI 2 (HDMI 2.0/HDCP 2.2, HDMI 1.4/HDCP 1.4) Audio-out (3.5mm) 1 Speaker 15W x2 USB Type A (Power) 1 (5V/1.5A) Control RS232 1 (DB 9-pin male) Control RJ45 1 (LAN control) USB Type A (Services) 1 (Shared with USB A Output) Power Supply Voltage 100-240V +/- 10%, 50/60Hz (AC in) Power Consumption Normal: 245W, Standby: <0.5W Operating Temperature 0~40 Carton Brown Net Weight 4.77kg Gross Weight 6.7kg Dimensions (WxDxH) 337x280x132mm (with Adjustment Foot) Packing Dimensions 496x387x195mm OSD Language 27 Languages User Guide Language 20 Languages Standard Accessories Power Cord: 1, Remote Control: 1, QSG: Yes, Warranty Card: Yes (CN Only)