



ViewSonic LS960WU 8,500 ANSI Lumens WUXGA Laser Installation Projector

SKU	LS960WU
Brand	ViewSonic
Stock	In stock

PRICING

Sign in to view pricing.

Description

Extended product overview

Introducing the LS960WU from ViewSonic's Luminous Superior Series, tailored for expansive venue displays. Featuring a robust 8,500 ANSI Lumens brightness and high native contrast provided by a 0.67" DMD chip through DLP technology, it delivers stunning visuals on screens up to 300 inches. Ideal for modern workplaces, its 21:9 aspect ratio is optimized for Microsoft Teams Rooms, enhancing collaborative environments. With a 1.6x optical zoom, it allows for a flexible setup to suit various installation needs, and the motorized focus, lens shift, and H/V keystone adjustment make the process a breeze. Additionally, portrait mode and 360° projection capabilities cater to more advanced requirements. Comprehensive LAN control ensures seamless integration into existing device management networks. Employing advanced 2nd generation laser phosphor technology, the LS960WU boasts a remarkable 30,000-hour lifespan, reducing maintenance costs for both business and educational institutions. Key Features: 8,500 ANSI Lumens ensuring vibrant images in large venues High native contrast ratio provided by a 0.67" DMD chip and DLP technology Supports 21:9 aspect ratio, ideal for Microsoft Teams Rooms Installation flexibility: motorized focus, 1.6x optical zoom, H/V lens shift, and 360° projection Centralized LAN control for efficient management 2nd generation laser phosphor technology with up to 30,000-hour lifespan Specification Details Projection System 0.67" WUXGA Native Resolution 1920x1200 Brightness 8500 (ANSI Lumens) Brightness (Center Lumens) 8800 Contrast Ratio 3000000:1 Display Color 1.07 Billion Colors Light Source Type Laser Phosphor Light Source Life (Normal Mode) 20000 hours Light Source Life (SuperEco Mode) 30000 hours Lens F=2.0-2.4, f=18.72-29.59mm Projection Offset 0%±10% Throw Ratio 1.25-2.00 Optical Zoom 1.6X Digital Zoom 0.5x-4.0x Image Size 50"-300" Throw Distance 1.33-13.06m (100"@2.70m) Keystone H:±30°, V:±30° Lens Shift V. Range +55%, -55% Lens Shift H. Range +25%, -25% Audible Noise (Normal) 32dB Audible Noise (Eco) 30dB Input Lag 19ms Resolution Support VGA(640 x 480) to 4K(3840 x 2160) HDTV Compatibility 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p Horizontal Frequency 15K-135KHz Vertical Scan Rate 23-120Hz Inputs Computer in: 1, HDMI: 2 (HDMI 2.0/HDCP 1.4/2.2), Audio-in (3.5mm): 1, 3D VESA (Sync): 1, HDBaseT: 1, IR In: 1 Outputs HDMI out: 1, Audio-out (3.5mm): 1, Speaker: 10W x2, 12V Trigger: 1, 3D SYNC Out: 1 Control RS232: 1, RJ45 (LAN): 1, Wired Remote Control In: 1 Power Supply Voltage 100-240V±10%, 50/60Hz (AC in) Power Consumption Normal: 545W, Standby: <0.5W Net Weight 13.7kg Gross Weight 18.4kg Dimensions (WxDxH) 486x433x186mm Packing Dimensions 654x563x373mm OSD Language 24 Languages User Guide Language 20 Languages Standard Accessories Power Cord: 1, Remote Control: 1 (w/backlit), QSG: Yes, Warranty Card: Yes (CN Only)