



ViewSonic LSC521WU 5,200 ANSI Lumens WUXGA Laser Installation Projector

SKU	LSC521WU
Brand	ViewSonic
Stock	In stock

PRICING

Sign in to view pricing.

Description

Extended product overview

The LSC521WU is a lamp-free, high-brightness projector designed for commercial, educational, and public spaces. Utilizing 3rd generation laser phosphor technology, this projector delivers 5,200 ANSI Lumens of brightness for up to 30,000 hours and can project an ultra-large screen up to 300" in WUXGA resolution. Ideal for modern workplaces, its 21:9 aspect ratio is optimized for Microsoft Teams Rooms applications, enhancing collaborative environments. Equipped with features like V lens shift, 1.6x optical zoom, H/V keystone correction, and 360° projection capabilities, the LSC521WU offers flexible setup possibilities. Additionally, its comprehensive LAN control ensures seamless integration into existing device management networks. Key Features: 5,200 ANSI Lumens offering bright images in any environment Up to a 300" ultra-large screen with a lower cost-per-inch Supports a 21:9 aspect ratio, ideal for Microsoft Teams Rooms Installation flexibility: V lens shift, 1.6x optical zoom, and H/V keystone correction 3rd generation laser phosphor technology with a lifespan up to 30,000 hours Centralized LAN control for efficient management Specification Details Projection System 0.67" WUXGA Native Resolution 1920x1200 Brightness 8500 (ANSI Lumens) Brightness (Center Lumens) 8800 Contrast Ratio 3000000:1 Display Color 1.07 Billion Colors Light Source Type Laser Phosphor Light Source Life (Normal Mode) 20000 hours Light Source Life (SuperEco Mode) 30000 hours Lens F=2.0-2.4, f=18.72-29.59mm Projection Offset 0%±10% Throw Ratio 1.25-2.00 Optical Zoom 1.6X Digital Zoom 0.5x-4.0x Image Size 50"-300" Throw Distance 1.33-13.06m (100"@2.70m) Keystone H:±/-30°, V:±/-30° Lens Shift V. Range +55%, -55% Lens Shift H. Range +25%, -25% Audible Noise (Normal) 32dB Audible Noise (Eco) 30dB Input Lag 19ms Resolution Support VGA(640 x 480) to 4K(3840 x 2160) HDTV Compatibility 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p Horizontal Frequency 15K-135KHz Vertical Scan Rate 23-120Hz Inputs Computer in: 1, HDMI: 2 (HDMI 2.0/HDCP 1.4/2.2), Audio-in (3.5mm): 1, 3D VESA (Sync): 1, HDBaseT: 1, IR In: 1 Outputs HDMI out: 1, Audio-out (3.5mm): 1, Speaker: 10W x2, 12V Trigger: 1, 3D SYNC Out: 1 Control RS232: 1, RJ45 (LAN): 1, Wired Remote Control In: 1 Power Supply Voltage 100-240V±/ 10%, 50/60Hz (AC in) Power Consumption Normal: 545W, Standby: <0.5W Net Weight 13.7kg Gross Weight 18.4kg Dimensions (WxDxH) 486x433x186mm Packing Dimensions 654x563x373mm OSD Language 24 Languages User Guide Language 20 Languages Standard Accessories Power Cord: 1, Remote Control: 1 (w/ backlit), QSG: Yes, Warranty Card: Yes (CN Only)