



ViewSonic LSC601-4K 6,000 ANSI Lumens 4K Laser Installation Projector

SKU	LSC601-4K
Brand	ViewSonic
Stock	In stock

PRICING

Sign in to view pricing.

Description

Extended product overview

The LSC601-4K is a lamp-free, high-brightness projector designed for commercial, educational, and public spaces. Equipped with 4K resolution and HDR/HLG support, it delivers professional-quality presentations and stunning visuals. Utilizing 2nd generation laser phosphor technology, this projector offers 6,000 ANSI Lumens of brightness for up to 30,000 hours and can project an ultra-large screen up to 300". Ideal for modern workplaces, its 21:9 aspect ratio is optimized for Microsoft Teams Rooms applications, enhancing collaborative environments. Equipped with features like H/V lens shift, 1.6x optical zoom, H/V keystone correction, and 360° projection capabilities, the LSC601-4K offers flexible setup possibilities. Additionally, its comprehensive LAN control ensures seamless integration into existing device management networks. Key Features: 4K HDR professional-quality visuals 6,000 ANSI Lumens offering bright images in any environment Up to a 300" ultra-large screen with a lower cost-per-inch Supports a 21:9 aspect ratio, ideal for Microsoft Teams Rooms Installation flexibility: H/V lens shift, 1.6x optical zoom, and H/V keystone correction 2nd generation laser phosphor technology with a lifespan up to 30,000 hours Centralized LAN control for efficient management Specification Details Projection System 3LCD (3x0.64" with MLA) Native Resolution WUXGA with 4K Enhancement Brightness 6000 (ANSI Lumens) Brightness (Center Lumens) 6500 Contrast Ratio 3000000:1 Display Color 1.07 Billion Colors Light Source Type Laser Phosphor Light Source Life (Normal Mode) 20000 hours Light Source Life (SuperEco Mode) 30000 hours (Eco) Lens F=1.5-2.08, f=17.2-27.7mm Projection Offset 0%±5% Throw Ratio 1.2-2.0 Optical Zoom 1.6X Digital Zoom 1.0x-2.0x Image Size 30"-300" Throw Distance 0.80-13.35m (100"@2.66m) Keystone H:±25°, V:±30° Lens Shift V. Range +66%, 0% Lens Shift H. Range +29%, -29% Audible Noise (Normal) 37dB Audible Noise (Eco) 26dB Input Lag 32ms Resolution Support VGA(640 x 480) to 4K(3840 x 2160) HDTV Compatibility 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p Horizontal Frequency 15K-135KHz Vertical Scan Rate 24-85Hz Inputs HDMI: 2 (HDMI 2.0, HDCP 1.4/2.2), Audio-in (3.5mm): 1, USB Type A: 2 (5V/2A), HDBaseT: 1, RJ45 Input (Internet): Yes Outputs Audio-out (3.5mm): 1, Audio-out (HDMI ARC): 1 (Share with HDMI Input), S/PDIF: 1, Speaker: 16W, USB Type A (Power): 2 Control RS232: 1, RJ45 (LAN Control): 1, USB Type A (Services): 1 Power Supply Voltage 100-240V±10%, 50/60Hz (AC in) Power Consumption Normal: 325W, Standby: <0.5W Net Weight 7.9kg Gross Weight 10.10kg Dimensions (WxDxH) 405x358x137mm Packing Dimensions 510x498x260mm OSD Language 23 Languages User Guide Language 20 Languages Standard Accessories Power Cord: 1, Remote Control: 1, QSG: Yes, Air Filter: Yes, Warranty Card: Yes (CN Only)