



Viewsonic LSC601WU 6,000 ANSI Lumens WUXGA Laser Projector

SKU	LSC601WU
Brand	ViewSonic
Stock	In stock

PRICING

Sign in to view pricing.

Description

Extended product overview

OVERVIEW The LSC601WU is a lamp-free, high-brightness projector designed for commercial, educational, and public spaces. Utilizing 2nd generation laser phosphor technology, this projector delivers 6,000 ANSI Lumens of brightness for up to 30,000 hours and can project an ultra-large screen up to 300" in WUXGA resolution. Ideal for modern workplaces, its 21:9 aspect ratio is optimized for Microsoft Teams Rooms applications, enhancing collaborative environments. Equipped with features like H/V lens shift, 1.6x optical zoom, H/V keystone correction, and 360° projection capabilities, the LSC601WU offers flexible setup possibilities. Additionally, its comprehensive LAN control ensures seamless integration into existing device management networks.

Key Features 6,000 ANSI Lumens offering bright images in any environment Up to a 300" ultra-large screen with a lower cost-per-inch Supports a 21:9 aspect ratio, ideal for Microsoft Teams Rooms Installation flexibility: H/V lens shift, 1.6x optical zoom, and H/V keystone correction 2nd generation laser phosphor technology with a lifespan up to 30,000 hours Centralized LAN control for efficient management Bright Images for Large Venues Delivering 6,000 ANSI Lumens, the projector provides vibrant and sharp projection in all lighting conditions, making it ideal for boardrooms, lecture halls, galleries, and other expansive spaces. Ultra-large Screen with Lower Cost-per-inch This easy-to-install projector allows for an image size of up to 300", offering a lower cost-per-inch compared to other types of commercial displays. Next-Gen Meeting Experience with 21:9 Aspect Ratio The projector supports a 21:9 aspect ratio, tailored for Microsoft Teams Rooms (MTR) in front-row mode. This widescreen format enhances meeting experiences by simultaneously displaying the presentation, chat, notifications, and participant video feeds. Adaptable to Any Environment Featuring tool-free lens shift control knobs, 1.6x optical zoom, H/V keystone correction, and 4-corner adjustment, this projector allows easy image adjustments without relocation, ensuring it fits any environment. 2nd Generation Laser Phosphor Technology This technology improves brightness by 20%, offers better heat-resistance, and a more compact design for increased reliability. Centralized Control for Management Efficiency The projector is compatible with Crestron, PJ Link, ATEN, and Extron systems, allowing for centralized device management.

Dimensions & I/O Ports Zoom Ring Focus Ring Front IR Rear IR RJ45 Service USB-A (5V/2A) HDMI x2 Computer HDBaseT Monitor Out Audio Out Audio In RS232 AC In LED Indicator Keypad Lens Shift Control Knob x2

SPECIFICATION Projection System System: 3LCD (3x0.64" with MLA) Native Resolution: 1920x1200 Brightness: 6000 (ANSI Lumens) Brightness (Center Lumens): 6500 Contrast Ratio: 3,000,000:1 Display Color: 1.07 Billion Colors Light Source Type: Laser Phosphor Life (Normal Mode): 20,000 hours Life (SuperEco Mode): 30,000 hours Lens F-Stop: F=1.58-2.02 Focal Length: f=15.3-24.6mm Projection Details Projection Offset: 0% +/- 5% Throw Ratio: 1.08-1.76 Optical Zoom: 1.6X Digital Zoom: 1.0x-4.0x Image Size: 30"-300" Throw Distance: 0.70-11.37m (100"@2.33m) Keystone Correction: H:+/-30°, V:+/-30° Lens Shift (Vertical): +45%, 0% Lens Shift (Horizontal): +21%, -21% Performance Audible Noise (Normal): 35dB Audible Noise (Eco): 25dB Input Lag: 60ms Resolution Support: VGA (640x480) to 4K (3840x2160) HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p Horizontal Frequency: 15K-100KHz Vertical Scan Rate: 23-85Hz Input Computer In (share with component): 1 HDMI: 2 (HDMI 1.4/HDCP 1.4) Audio-in (3.5mm): 1 USB Type A: 1 (5V/2A) HDBaseT: 1 Output Monitor Out: 1 Audio-out (3.5mm): 1 Speaker: 16W USB Type A (Power): 1 (USB 2.0 - 5V/2A, shares with USB A Input) Control RS232 (DB 9-pin male): 1 RJ45 (LAN control): 1 USB Type B (Services): 1 Other Specifications Power Supply Voltage: 100-240V +/- 10%, 50/60Hz (AC in) Power Consumption: Normal: 330W, Standby: <0.5W Operating Temperature: 0~40°C Carton: Brown Net Weight: 7.9kg Gross Weight: 10.93kg Dimensions (WxDxH) with Adjustment Foot: 405x358x137mm Packing Dimensions: 510x498x260mm OSD Language Support English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portuguese, Japanese, Simplified Chinese, Traditional Chinese, Korean, Russian, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese, Thai, Farsi (25 languages) User Guide Language Support English, Simplified Chinese, Traditional Chinese, Indonesian, Finnish,

French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese (20 languages) Standard Accessories Power Cord: 1 Remote Control: 1 Quick Start Guide: Yes Air Filter: Yes Warranty Card: Yes (CN only) Optional Accessories Air Filter: Yes Wall/Ceiling Mount: PJ-WMK-007

Generated automatically from live product data. Pricing and availability may change. This datasheet is valid for 7 days from the date of generation.

Graystone