



ViewSonic LSC801WU 8,000 ANSI Lumens WUXGA Laser Installation Projector

SKU	LSC801WU
Brand	ViewSonic
Stock	In stock

PRICING

Sign in to view pricing.

Description

Extended product overview

The LSC801WU is a lamp-free, high-brightness projector designed for commercial, educational, and public spaces. Utilizing 2nd generation laser phosphor technology, this projector delivers 8,000 ANSI Lumens of brightness for up to 30,000 hours and can project an ultra-large screen up to 300" in WUXGA resolution. Ideal for modern workplaces, its 21:9 aspect ratio is optimized for Microsoft Teams Rooms applications, enhancing collaborative environments. Equipped with features like H/V lens shift, 1.6x optical zoom, H/V keystone correction, and 360° projection capabilities, the LSC801WU offers flexible setup possibilities. Additionally, its comprehensive LAN control ensures seamless integration into existing device management networks. Key Features: 8,000 ANSI Lumens offering bright images in any environment Up to a 300" ultra-large screen with a lower cost-per-inch Supports a 21:9 aspect ratio, ideal for Microsoft Teams Rooms Installation flexibility: H/V lens shift, 1.6x optical zoom, and H/V keystone correction 2nd generation laser phosphor technology with a lifespan up to 30,000 hours Centralized LAN control for efficient management Specification Details Projection System 3LCD (3x0.64" with MLA) Native Resolution 1920x1200 Brightness 8000 (ANSI Lumens) Brightness (Center Lumens) 8500 Contrast Ratio 3000000:1 Display Color 1.07 Billion Colors Light Source Type Laser Phosphor Light Source Life (Normal Mode) 20000 hours Light Source Life (SuperEco Mode) 30000 hours (Eco) Lens F=1.5-2.08, f=17.2-27.7mm Projection Offset 0%±5% Throw Ratio 1.2-2.0 Optical Zoom 1.6X Digital Zoom 1.0x-4.0x Image Size 30"-300" Throw Distance 0.78-12.99m (100"@2.58m) Keystone H:±/-25° V:±/-30° Lens Shift V. Range +60%, 0% Lens Shift H. Range +29%, -29% Audible Noise (Normal) 37dB Audible Noise (Eco) 27dB Input Lag 60ms Resolution Support VGA(640 x 480) to 4K(3840 x 2160) HDTV Compatibility 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p Horizontal Frequency 15K-100KHz Vertical Scan Rate 23-85Hz Inputs Computer in: 1, HDMI: 2 (HDMI 1.4/ HDCP 1.4), Audio-in (3.5mm): 1, USB Type A: 1 (5V/2A), HDBaseT: 1 Outputs Monitor out: 1, Audio-out (3.5mm): 1, Speaker: 16W, USB Type A (Power): 1 Control RS232: 1, RJ45 (LAN Control): 1, USB Type B (Services): 1 Power Supply Voltage 100-240V+/- 10%, 50/60Hz (AC in) Power Consumption Normal: 385W, Standby: <0.5W Net Weight 7.9kg Gross Weight 10.93kg Dimensions (WxDxH) 405x358x137mm Packing Dimensions 510x498x260mm OSD Language 25 Languages User Guide Language 20 Languages Standard Accessories Power Cord: 1, Remote Control: 1, QSG: Yes, Air Filter: Yes, Warranty Card: Yes (CN Only)