



PRODUCT OVERVIEW

## ViewSonic LSD300W-ST 3,300 ANSI Lumens WXGA Short Throw LED Education Projector

ViewSonic • SKU LSD300W-ST



## ViewSonic LSD300W-ST 3,300 ANSI Lumens WXGA Short Throw LED Education Projector

SKU	LSD300W-ST
Brand	ViewSonic
Stock	In stock

### PRICING

Sign in to view pricing.

## Description

Extended product overview

The LSD300W-ST is a short-throw LED projector from ViewSonic, designed specifically for education environments. It delivers 3,300 ANSI Lumens of brightness and WXGA resolution, making it ideal for small to medium-sized classrooms. With a 0.49 short-throw ratio, it projects a 100" image from just 1.06 meters, ensuring clear visuals with minimal glare and shadows. Powered by third-generation LED technology, this lamp-free projector offers a 60,000-hour lifespan, helping reduce maintenance costs and eliminate the use of mercury-based lamps. Its sealed DLP engine ensures dustproof, filter-free operation with long-lasting colour performance. Designed for intuitive operation, the LSD300W-ST features instant power on/off, horizontal/vertical keystone correction, 4-corner adjustment, and 360° projection, making it suitable for versatile installations—including floor projection in education settings. A built-in LAN control interface streamlines centralised device management and supports integration with Crestron, Extron, and ATEN systems. Key Features: Advanced 3rd-gen LED tech with a 60,000-hour lifespan for low maintenance and reliable performance 0.49 short throw & 360° projection ensure glare-free visuals and flexible installation anywhere IP5X-sealed DLP engine ensures a dustproof, filter-free system for consistent colour performance LAN control for easy remote and centralised management User-friendly setup with instant on/off, H/V keystone correction, and 4-corner adjustment 3,300 ANSI Lumens & high native contrast ratio powered by a 0.65" DMD chip for sharp visuals Specification Projection System 0.65" WXGA Native Resolution 1280 × 800 (WXGA) Brightness 3,300 ANSI Lumens Brightness (Center Lumens) 3,700 Lumens Contrast Ratio 3,000,000:1 Display Color 1.07 Billion Colors Light Source Type LED Light Source Life (Normal) 60,000 hours Lens F=2.6, f=6.9mm Projection Offset 110% ±5% Throw Ratio 0.49 Optical Zoom Fixed Digital Zoom 0.8x–2.0x Image Size 60"–300" Throw Distance 0.63–1.58 m (87" @ 0.92 m) Keystone H: ±40°, V: ±40° Audible Noise (Normal) 32 dB Audible Noise (Eco) 27 dB Input Lag 16 ms Resolution Support VGA (640×480) to Full HD (1920×1080) HDTV Compatibility 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Horizontal Frequency 15 kHz–102 kHz Vertical Scan Rate 23–120 Hz Interactive Camera Optional (vTouch-10s) Input Computer In (shared with Component) 1 HDMI 1 (HDMI 1.4, HDCP 1.4) Audio-in (3.5 mm) 1 Output Monitor Out 1 Audio-out (3.5 mm) 1 Speaker 2 W USB Type-A (Power) 1 (5V / 2A) Control RS232 (DB 9-pin male) 1 RJ45 (LAN Control) 1 USB Type-A (Service) 1 (shared with USB-A Output) Others Power Supply Voltage 100–240 V ±10%, 50/60 Hz (AC in) Power Consumption Normal: 255 W; Standby: < 0.5 W Operating Temperature 0–40 °C Carton Brown Net / Gross Weight 2.85 kg / 3.80 kg Dimensions (WxDxH) with Feet 294 × 237 × 115 mm Packing Dimensions 365 × 300 × 188 mm OSD Languages 24 total (English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, Traditional Chinese, Simplified Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Hindi, Arabic, Vietnamese, Greek, Hungarian) User Guide Languages 20 total (English, Simplified Chinese, Traditional Chinese, Indonesian, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese) Standard Accessory Power Cord 1 VGA Cable 1 Remote Control 1 QSG (Quick Start Guide) Yes Lens Cover Yes Warranty Card Yes (CN Only) Optional Accessory Wall/Ceiling Mount PJ-WMK-305 / PJ-WMK-007 Carry Bag PJ-CASE-008