



## ViewSonic PA504W 4,000 ANSI Lumens WXGA Education & Business Projector

SKU	PA504W
Brand	ViewSonic
Stock	In stock

PRICING

Sign in to view pricing.

## Description

Extended product overview

The ViewSonic PA504W is a high-brightness lamp projector tailored for both education and business settings. It features a 1.21-1.57 throw ratio, allowing seamless projector upgrades in typical installation conditions. With 4000 ANSI Lumens, it ensures bright, vivid images even in well-lit environments, guaranteeing clarity for every presentation or lesson. Its Texas Instruments' 0.65" DMD Chip elevates the viewing experience with a high native contrast ratio, unveiling fine details for exceptional sharpness on the screen. Effortlessly switch between content sources via the dual HDMI ports. Additionally, you can combine it with the ViewSonic WPD-700 Wireless Screen Casting Kit, powered by the projector's USB-A output, for expanded versatility. Comprehensive LAN control takes this convenience further, providing streamlined device management. Based on DLP technology, it maintains consistent color performance and great readability over time and features a filter-free design for minimal maintenance requirements.

**Key Features:** 1.21-1.57 throw ratio enables seamless projector upgrades 4,000 ANSI Lumens offering bright images in any environment Convenient connectivity with dual HDMI and USB-A power supply Comprehensive LAN control for centralized device management High native contrast ratio achieved through Texas Instruments' 0.65" DMD chip DLP technology offering filter-free design and consistent image quality

**Specification Details**

**Projection System**  
0.65" WXGA Native Resolution 1280x800 Brightness 4000 (ANSI Lumens) Contrast Ratio (SuperEco Mode) 22000:1 Display Color 1.07 Billion Colors Light Source Type 200W UHP Lamp Light Source Life (Normal Mode) 6000 hours Light Source Life (SuperEco Mode) 15000 hours Lens F=2.59-2.87, f=16.88-21.88mm Projection Offset 120%±5% Throw Ratio 1.21-1.57 Optical Zoom 1.3x Digital Zoom 0.8x-2.0x Image Size 30"-300" Throw Distance 0.78m-10.14m (100"@2.61m) Keystone V:±40° Audible Noise (Normal) 31dB Audible Noise (Eco) 27dB Input Lag 16ms Resolution Support VGA(640 x 480) to FullHD(1920 x 1080) HDTV Compatibility 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM Horizontal Frequency 15K-102KHz Vertical Scan Rate 23-120Hz Inputs Computer in: 1, Composite: 1, HDMI: 2 (HDMI 1.4/ HDCP 1.4), Audio-in (3.5mm): 1 Outputs Monitor out: 1, Audio-out (3.5mm): 1, Speaker: 10W USB Type A (Power) 1 (5V/1.5A) Control RS232: 1, RJ45: 1, USB Type A (Services): 1 Power Supply Voltage 100-240V±10%, 50/60Hz Power Consumption Normal: 255W, Standby: &lt;0.5W Net Weight 2.33kg Gross Weight 3.54kg Dimensions (WxDxH) 294x218x110mm Packing Dimensions 415x168x297mm OSD Language 23 Languages User Guide Language 20 Languages Standard Accessories Power Cord: 1, VGA Cable: 1, Remote Control: 1, QSG: Yes, Warranty Card: Yes (CN Only)